



IC03



IV03

SIP Safety Intercom

ZYCOO SIP Safety Intercom IV03 and IC03 are compact PoE enabled intercom devices equipped with a PTT (Press to Talk) button. IV03 is mainly used for voice intercom but can be linked with an external IP camera for video intercom. IC03 can do video intercom with its built-in HD camera. Both of them can be easily integrated with any SIP server for full-duplex communication. Additionally, access control is enabled on both of them.

Applicable Scenarios



Schools



Office Buildings



Health Care



Residential Buildings



Industrial Facilities



Warehouses



Manufacture Facilities



Parking Garages



Government Offices



Highway



Energy Industry



Financial Institution

Features

- Support standard SIP protocol, can be integrated with ZYCOO IP Audio Center and third-party SIP server for Press-to-Talk functionality. The PTT key can be programmed with any desired number, internal SIP number or external phone number.
- Support G.722 wideband audio codec, provides clear and intelligible voice speech for the intercom calls. With the high audio reproduction ability and clarity, quality of communication is guaranteed even in a noisy environment.
- Support video intercom, IC03 has built-in HD camera, IV03 can be linked with external IP camera. Voice and video intercom can be achieved easily with flexible choices.
- Support access control, door strike can be connected and controlled by sensor input signal, DTMF single during the intercom call or by the call status events.
- Support auto provisioning and centralized management by ZYCOO IP Audio Center, either the devices are deployed in local LAN or on remote site. It will be time and effort saving especially for the large-scale installations.
- Standard PoE (IV03: IEEE 802.3af/at; IC03:IEEE802.3at) support, simple and easy installation with a single network cable. External power supply can be used if required.

Specifications

	IV03	IC03
Speaker		
Speaker Component:	Ø 40 mm x 12.7 mm (1.6 x 0.5 in)	
Sensitivity:	90±3dB	
Distortion:	<10%,1000Hz 0.1W/1M	
Rated Power:	3W	
Maximum power:	4W	
Frequency Range:	630Hz – 4.5KHz	
Acoustics:	Mono	
Microphone		
Microphone	-36±2dB RL=2.2K Vs=2.0V	
Audio Compression		
Audio Codecs:	G.722, G.711 A-law, G.711 U-law, G.729	
Music Streaming:	MP3 sampling rate 8 – 48KHz, bit rate 64 – 320kpbs, mono or Stereo	

Video		
Camera	N/A	1920*1080@20fps, 1280*720@25fps
Video Codec	N/A	H.264
Network		
Network Interface	10/100Mbps,PoE IEEE802.3af/at	10/100Mbps,PoE IEEE802.3at
Protocols	HTTP, HTTPS, IPV4, SSL, QoS Layer3 DiffServ, SFTP, FTP, DNS, SNMP, NTP RTSP, RTMP, RTP, RTCP, TCP, UDP, MQTT, ICMP, DHCP, ARP, SSH, SIP	
Door Control		
Door Control	NO/NC Contacts, Max AC 125V-1A/DC 60V-1A	
Administration		
Configuration:	Web interface or auto provisioning server	
Provisioning method:	MQTT IoT Protocol	
Mechanical Properties		
Memory:	128MB RAM, 256MB Flash	
Power input:	PoE IEEE802.3af/at or DC12V1A	PoE IEEE802.3at or DC12V2A
Casing:	Surface-treated steel	
Color:	Silver	
Weight:	473g	476g
Dimension:	164*80*40mm	164*80*44mm
Mounting method:	Wall mounted	
Key:	Silver button with blue backlight, press to call, press and hold for 5 seconds to announce IP address	
Environmental		
Installation Environment:	Indoor	
Operating temperature:	-20°C - 50°C (-4°F - 122°F)	
Storage temperature:	-40°C - 70°C (-40°F - 158°F)	
Humidity:	10% - 95% RH Non-condensing	
Approvals		
Approvals:	EN 55032:2015, EN 55035:2017, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 62368-1:2014+A11:2017, FCC Part 15B Class A	